



Semi Auto Edge Banding Machine

DESCRIPTION OF PRODUCT

Hot Melt Glue 140 is a high performance product from Germany. It is a thermoplastic hotmelt adhesive with medium tack and medium open time. It is able to operate under temperature as low as **140°C**. It is used during edge banding application.

TYPICAL APPLICATIONS

Hot Melt Glue 140 is recommended for PVC, ABS and veneer edge banding application to particle board, MDF board & wood panel.

TECHNICAL CHARACTERISTICS

Application Temperature	:	130°C - 150°C
Feed Speed	:	5 - 15 m/min
Colour	:	Beige
Form	:	Granules
Softening Range	:	Approx 75°C
Storage	:	12 months in cool and dry enrichment
Packaging	:	25 kgs / Bag
Country Origin	:	Made in Germany





Auto Edge Banding Machine

DESCRIPTION OF PRODUCT

Hot Melt Glue 180 is a high performance product from Germany. It is a thermoplastic hotmelt adhesive with high tack and medium open time. It is used during edge banding application.

TYPICAL APPLICATIONS

Hot Melt Glue 180 is recommended for PVC, ABS and veneer edge banding application to particles board, MDF board & wood panel.

TECHNICAL CHARACTERISTICS

Application Temperature	: 180°C - 200°C
Feed Speed	: 10 - 30 m/min
Colour	: Beige
Form	: Granules
Softening Range	: Approx 90°C
Storage	: 12 months in cool and dry enrichment
Packaging	: 25 kgs / Bag
Country Origin	: Made in Germany

